



PHOENIX DISPLAY INTERNATIONAL, INC.

PHOENIX DISPLAY INTERNATIONAL, INC

SPECIFICATION FOR LCD MODULE

CUSTOMER	
PART NUMBER	PDI050YVHR01
DESCRIPTION	5.0" 480 (RGB) x 800
VERSION	1.0
ISSUE DATE	07-Feb-19

COMPANY ADDRESS:

Phoenix Display International, Inc.
6150 W. Gila Springs Place Unit 2
Chandler, AZ 85226
USA
www.phoenixdisplay.com
(630) 359-5700 office
(630) 359-5701 fax

Table of Contents

Table of Contents	2
Record of Revision.....	3
1 General Specifications.....	4
2 Input/Output Terminals	5
3 Absolute Maximum Ratings.....	7
4 Electrical Characteristics	8
5 Timing Chart.....	10
6 Optical Characteristics(with CTP).....	12
7 Optical Characteristics(without CTP).....	14
8 Environmental / Reliability Test.....	19
9 Mechanical Drawing.....	20
10 Packing Drawing	21
11 Precautions for Use of LCD Modules.....	21

1 General Specifications


	Feature	Spec
Display Spec.	Size	5.0"
	Resolution	480(RGB)x800
	Technology Type	a-si TFT
	Pixel Configuration	RGB Vertical Stripe
	Pixel pitch(mm)	0.135X0.135
	Display Mode	ECB, full reflective
	Surface Treatment	HC
	Viewing Direction(IC at 6 o'clock)	2o'clock
Gray Scale Inversion Direction	8o'clock	
TP Spec	Operation Technology	Projected capacitive (Self / Mutual mode)
	Control IC	Elan Ektf2145pw
	Input Method	Finger & glove
	Number of simultaneous touches	2 points multi-touch
	Minimum Touch Area(mm)	Φ7mm
	Finger Pitch(mm)	16
	Product structure	G+G
	Interface	I2C
AF	Before rubbing : water contact angle > 110° ; After rubbing: 1kg loader, 3000 cycles, #0000 steel wool : water contact angle > 100°	
Mechanical Characteristics	LCM (W x H x D) (mm)	80.41X140.6X5.78
	Active Area(mm)	64.8x108.00
	With /Without TSP	With CTP
	Matching Connection Type	JACS-FB10S051JT1
	LED Numbers	10LEDs
	Weight (g)	TBD
Electrical Characteristics	Interface	MCU 16bit
	Color Depth	65K
	Driver IC	ILI9806

Note 1: Viewing direction for best image quality is different from TFT definition. There is a 180 degree shift.

Note 2: Requirements on Environmental Protection: Q/S0002

Note 3: LCM weight tolerance: ± 5%

Note 4 : Top polarizer absorption angle as follow:



2 Input/Output Terminals

Matched connector: JACS-FB10S051JT1

Pin No.	Symbol	I/O	Function	Remark
1	LEDA	P	Power supply for LED(Anode)	
2	LEDA	P	Power supply for LED (Anode)	
3	NC	-	No connection	
4	NC	-	No connection	
5	NC	-	No connection	
6	LEDK1	P	Power supply for LED(Cathode)	
7	LEDK2	P	Power supply for LED(Cathode)	
8	NC	-	No connection	
9	GND	P	Ground	
10	ID1	O	ID pin	<i>Connect GNG</i>
11	ID2	O	ID pin	<i>Connect GNG</i>
12	LEDPWM	O	The PWM Frequency output for LED driver control .	
13	GND	P	Ground	
14	GND	P	Ground	
15	DB0	I	Data signal	
16	DB1	I	Data signal	
17	DB2	I	Data signal	
18	DB3	I	Data signal	
19	DB4	I	Data signal	
20	DB5	I	Data signal	
21	DB6	I	Data signal	
22	DB7	I	Data signal	
23	DB8	I	Data signal	
24	DB9	I	Data signal	
25	DB10	I	Data signal	
26	DB11	I	Data signal	
27	DB12	I	Data signal	
28	DB13	I	Data signal	
29	DB14	I	Data signal	

30	DB15	I	Data signal	
31	GND	P	Ground	
32	GND	P	Ground	
33	RESET	I	Reset input pin	
34	VDD	P	Supply voltage	2.8V
35	VDD	P	Supply voltage	2.8V
36	NC	-	No connection	
37	GND	P	Ground	
38	IOVCC	P	Supply voltage(I/O)	1.8V
39	CS	I	A chip select signal	
40	DC	I	The signal for command or	
41	RD	I	Serves as a read signal and read data at the rising edge	
42	WR	I	Serves as a write signal and writes data at the rising	
43	TE	O	Tearing effect signal pin	
44	GND	P	Ground	
45	GND	P	Ground	
46	TP_VCC	P	Supply voltage for CTP	
47	TP_INT	O	External interrupt from the host	
48	TP_SDA	I/O	I2C data input and output	
49	TP_SCL	I	I2C clock input	
50	TP_RST	I	Reset pin for CTP	
51	GND	P	Ground	

Note1: Please add the FPC connector type and matched one if necessary .

3 Absolute Maximum Ratings

GND=0V

Item	Symbol	MIN	MAX	Unit	Remark
Power Voltage	VCC	-0.3	4.6	V	Note1
Input voltage	VDD	-0.3	4.6	V	
Operating Temperature	Top	-20	70	°C	
Storage Temperature	Tst	-30	85	°C	
Relative Humidity Note2	RH	--	≤95	%	Ta≤40°C
		--	≤85	%	40°C < Ta ≤ 50°C
		--	≤55	%	50°C < Ta ≤ 60°C
		--	≤36	%	60°C < Ta ≤ 70°C
		--	≤24	%	70°C < Ta ≤ 80°C
Absolute Humidity	AH	--	≤70	g/m ³	Ta > 70°C

Table 3 Absolute Maximum Ratings

Note1: Input voltage include R0~R5, G0~G5, B0~B5, Dotclk, Hsync, Vsync, Enable, R/L, U/D.

Note2: Ta means the ambient temperature.

It is necessary to limit the relative humidity to the specified temperature range.

Condensation on the module is not allowed.

4 Electrical Characteristics

4.1 LCD Module

GND=0V, Ta=25°C

Item	Symbol	MIN	TYP	MAX	Unit	Remark	
Logic Supply Voltage	IOVCC	1.7	1.8	1.9	V		
Analog Supply Voltage	VDD	2.7	2.8	2.9	V		
Input Signal Voltage	High Level	VIH	0.7 IOVCC	-	IOVCC	V	
	Low Level	VIL	-	-	0.3 IOVCC	V	
Output Signal Voltage	High Level	VOH	0.8 IOVCC	-	-	V	
	Low Level	VOL	-	-	0.2 IOVCC	V	

Table 4.1 LCD module electrical characteristics

4.2 CTP

GND=0V, Ta=25°C

Item	Symbol	MIN	TYP	MAX	Unit	Remark	
Logic Supply Voltage	TP_IOVCC	1.7		3.6	V		
Analog Supply Voltage	TP_VCC	3.0	3.3	3.6	V		
Input Signal Voltage	High Level	VIH	0.8 IOVCC	-	IOVCC	V	
	Low Level	VIL	-	-	0.2 IOVCC	V	

Table 4.1 CTP electrical characteristics

4.3 Backlight Unit(ME)

Ta=25°C

Item	Symbol	MIN	TYP	MAX	Unit	Remark
Forward Current	I _F	-	20	-	mA	One LED
Forward Voltage	V _F		5.65		V	One LED
Backlight Power Consumption	W _{BL}	-	1130	-	mW	10LEDs
Lifetime	T	-	15000	-	Hr	One LED
WLED part number	NS2W266G					

Table 4.2.1 backlight unit electrical characteristics




Figure 4.2.1 LED backlight circuit

4.3.1 Block Diagram





Figure 4.3 LCD module diagram

4.3.2 TP Circuit Block Diagram



5 Timing Chart

5.1 AC Characteristics




Table 5.1 3-line SPI AC Characteristics

5.2 SPI Interface Input Timing parameters

Signal	Symbol	Parameter	min	max	Unit	Description
CSX	t_{css}	Chip select time (Write)	15	-	ns	
	t_{csh}	Chip select hold time (Read)	15	-	ns	
	t_{chw}	CS "H" pulse width	40	-	ns	
SCL	t_{wc}	Serial clock cycle (Write)	30	-	ns	
	t_{wrh}	SCL "H" pulse width (Write)	10	-	ns	
	t_{wrl}	SCL "L" pulse width (Write)	10	-	ns	
	t_{rc}	Serial clock cycle (Read)	150	-	ns	
	t_{rdh}	SCL "H" pulse width (Read)	60	-	ns	
DCX	t_{rdl}	SCL "L" pulse width (Read)	60	-	ns	
	t_{as}	DCX setup time	10	-	ns	
SDA (Input)	t_{ah}	DCX hold time (Write/Read)	10	-	ns	
	t_{ds}	Data setup time (Write)	10	-	ns	
SDA (Output)	t_{dh}	Data hold time (Write)	10	-	ns	
	t_{acc}	Access time (Read)	10	50	ns	CL = 30pF (maximum)
	t_{oh}	Output disable time (Read)	15	50	ns	CL = 8pF (minimum)

Notes:

- $T_a = -30$ to 70°C , $V_{DDI} = 1.65\text{V}$ to 3.3V , $V_{DDA} = 2.6\text{V}$ to 4.8V , $V_{SSAM} = \text{GND} = 0\text{V}$, $T = 10 \pm 0.5\text{ns}$.
- Does not include signal rising and falling times.

Table 5.2 SPI Input Timing Parameters

5.3 Reset timing





Figure 5.4 Reset Timing Diagram

5.4 POWER ON/OFF SEQUENCE

VDDI and VDDA can be applied or powered down in any order. During the Power Off sequence, if the LCD is in the Sleep Out mode, VDDA and VDDI must be powered down with minimum 120msec. If the LCD is in the Sleep In mode, VDDA and VDDI can be powered down with minimum 0msec after the RESX is released. CSX can be applied at any timing or can be permanently grounded. RESX has high priority over CSX.



6 Optical Characteristics(with CTP)

6.1 Driving the backlight condition (Transmissive mode)

Item	Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles	θT	CR \geq 10	25	35	-	Degree	Note2,3
	θB		25	35	-		
	θL		15	25	-		
	θR		15	25	-		
Contrast Ratio	CR	$\theta=0^\circ$	30	40	-		Note 3
Response Time	T _{ON}	25℃	-	30	50	ms	Note 4
	T _{OFF}						
Chromaticity	White	Backlight is on	x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Red		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Green		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Blue		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
Uniformity	U		-	80%		%	Note 6
NTSC			15	20		%	Note 5
Luminance	L		120	150		cd/m ²	Note 7
Flicker					-25	dB	
Crosstalk					3%		

Test Conditions:

1. I_F= 20mA, and the ambient temperature is 25℃.
2. The test systems refer to Note 1 and Note 2.
3. Chromaticity is just for reference, please judge by the actually measurement.
4. Optical Characteristics (Backlight is on) tolerance is ± 0.04

6.2 Not Driving the backlight condition(Reflective mode)

Item	Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles	θT	CR \geq 2	45	55	-	Degree	Note2,3
	θB		45	55	-		
	θL		45	55	-		
	θR		45	55	-		
Contrast Ratio	CR	$\theta=0^\circ$	15	19	-		Note 3
Response Time	T _{ON}	25°C	10	20	40	ms	Note 4
	T _{OFF}						
Chromaticity	White	Backlight is off	x	0.284	0.314	0.344	Note 1,5
			y	0.334	0.364	0.394	
	Red		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Green		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Blue		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
Reflection ratio	U		15	19		%	Measure by DMS
NTSC			14.5	18.5		%	
Flicker					-30	dB	

Test Conditions:

1. I_F= 20 mA, and the ambient temperature is 25°C.
2. The test systems refer to Note 1 and Note 2.
3. Chromaticity is just for reference, please judge by the actually measurement.
4. Flicker pattern(pixel inversion: Line inversion)



Flicker for line inversion

7 Optical Characteristics(without CTP)

7.1 Driving the backlight condition (Transmissive mode)


Item	Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles	θT	CR \geq 10	25	35	-	Degree	Note2,3
	θB		25	35	-		
	θL		15	25	-		
	θR		15	25	-		
Contrast Ratio	CR	$\theta=0^\circ$	30	40	-		Note 3
Response Time	T_{ON}	25 $^\circ$ C	-	30	50	ms	Note 4
	T_{OFF}						
Chromaticity	White	Backlight is on	x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Red		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Green		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
	Blue		x	TBD	TBD	TBD	Note 1,5
			y	TBD	TBD	TBD	
Uniformity	U		-	80%		%	Note 6
NTSC			15	20		%	Note 5
Luminance	L		120	150		cd/m ²	Note 7
Flicker					-25	dB	
Crosstalk					3%		

7.2 Not Driving the backlight condition(Reflective mode)


Item	Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles	θT	CR \geq 2	45	55	-	Degree	Note2,3
	θB		45	55	-		
	θL		45	55	-		
	θR		45	55	-		
Contrast Ratio	CR	$\theta=0^\circ$	16	20	-		Note 3
Response Time	T _{ON}	25°C	10	20	40	ms	Note 4
	T _{OFF}						
Chromaticity	White	x	Backlight is off	0.280	0.310	0.340	Note 1,5
		y		0.330	0.360	0.390	
	Red	x		TBD	TBD	TBD	Note 1,5
		y		TBD	TBD	TBD	
	Green	x		TBD	TBD	TBD	Note 1,5
		y		TBD	TBD	TBD	
	Blue	x		TBD	TBD	TBD	Note 1,5
		y		TBD	TBD	TBD	
Reflection ratio	U		16	20		%	Measure by DMS
NTSC			16	20		%	
Flicker					-30	dB	

Note 1: Definition of optical measurement system.



1.Transsitive mode: The optical characteristics should be measured in dark room. After 5 Minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.




2. Reflective mode



Item	Photo detector	Field
Chromaticity	CM-3600A	
Contrast Ratio		
Viewing angle	DMS-803	
Flicker		
Reflective Ratio	DMS-803	



Note 2: Definition of viewing angle range and measurement system.
viewing angle is measured at the center point of the LCD.



Note 3: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD is on the "White" state}}{\text{Luminance measured when LCD is on the "Black" state}}$$


“White state “: The state is that the LCD should drive by V_{white} .

“Black state“: The state is that the LCD should drive by V_{black} .

V_{white} : To be determined V_{black} : To be determined.

Note 4: Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)


- (1) Color coordinates measured at center point of LCD.
- (2) For reflective mode color chromaticity we need to test at least 3 different batches to make sure the stability of panel and it accepts reasonable change after we get the stability data.

Note 6: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

Luminance Uniformity (U) = L_{min} / L_{max}

L-----Active area length W----- Active area width



L_{max} : The measured Maximum luminance of all measurement position.

L_{min} : The measured Minimum luminance of all measurement position.

Note 7: Definition of Luminance:

Measure the luminance of white state at center point.

Note 8: all the optical data is to meet garmin's requirements, it may adjust by first samples performance.

8 Environmental / Reliability Test


No	Test Item	Condition	Remarks
1	High Temperature Operation	Ta=+70°C, 240hrs	IEC60068-2-1:2007 GB2423.2-2008
2	Low Temperature Operation	Ta=-20°C, 240hrs	IEC60068-2-1:2007 GB2423.1-2008
3	High Temperature Storage	Ta=+85°C, 240hrs	IEC60068-2-1:2007 GB2423.2-2008
4	Low Temperature Storage	Ta=-30°C, 240hrs	IEC60068-2-1:2007 GB2423.1-2008
5	Storage at High Temperature and Humidity	Ta=+60°C, 90% RH 240 hours	IEC60068-2-78 :2001 GB/T2423.3—2006
6	Thermal Shock (non-operation)	-40°C 60 min~+85°C 60 min, Change time:5min, 50 Cycles	Start with cold temperature, End with high temperature, IEC60068-2-14:1984,GB 2423.22-2002
7	ESD	C=150pF, R=330Ω · 5points/panel Air:±6KV, 5times; Contact:±4KV, 5 times; (Environment: 15°C~35°C, 30%~60%, 86Kpa~106Kpa)	IEC61000-4-2:2001 GB/T17626.2-2006
8	Vibration Test	Frequency range:10~55Hz, Stroke:1.5mm Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z.	IEC60068-2-6:1982 GB/T2423.10—1995
9	Mechanical Shock (Non OP)	60G 6ms, ±X,±Y,±Z 3times, for each direction	IEC60068-2-27:1987 GB/T2423.5—1995
10	Package Drop Test	Height:60cm, 1corner,3edges,6surfaces	IEC60068-2-32:1990 GB/T2423.8—1995
11	Image sticking test	40° 6 hours judge without release	No Image sticking

Note1: Ta is the ambient temperature of sample.


Note2: Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

Note 3: In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

Note 4: Image sticking test is as below.



9 Mechanical Drawing



10 Packing Drawing

10.1 Packaging flow

TBD

11 Precautions for Use of LCD Modules

11.1 Handling Precautions

11.1.1 The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

11.1.2 If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

11.1.3 Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

11.1.4 The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

11.1.5 If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents

11.1.6 Do not attempt to disassemble the LCD Module.

11.1.7 If the logic circuit power is off, do not apply the input signals.

11.1.8 To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

10.1.8.1 Be sure to ground the body when handling the LCD Modules.

10.1.8.2 Tools required for assembly, such as soldering irons, must be properly ground.

10.1.8.3 To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

10.1.8.4 The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

11.2 Storage precautions

11.2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

11.2.2 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0°C ~ 40°C Relatively humidity: ≤80%

11.2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

11.3 Transportation Precautions

11.3.1 The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.

11.4 Bar Code definition on module

TBD